


Compression Coupler for Copper-Bonded Ground Rod, Pointed



- Threadless compression coupler for use with pointed copper-bonded ground rods
- Inside of coupler is tapered so ground rod compresses during installation to form an irreversible conductive connection



Material: Silicon Bronze



Part Number	Article Number	Ground Rod Diameter, Nominal	Length L	Unit Weight	Complies With
223CC12F	158000	1/2"	69.8 mm	0.13 kg	-
223CC58	158010	5/8"	69.8 mm	0.15 kg	IEC [*] EN 62561-2
223CC34	158020	3/4"	69.8 mm	0.20 kg	IEC [*] EN 62561-2

IEC^{*} EN 62561-2 supercedes EN 50164-2.

CSA, CSA-US and C-CSA-US are registered trademarks of Canadian Standards Association. IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.