


Stainless Steel Ground Rod, Threaded



- Utilizes a cut thread for highly corrosive soil



Tensile Strength: 483 MPa Min

Part Number	Ground Rod Diameter, Nominal	Ground Rod Diameter, Actual Ø	Thread Size TS	Length L	Unit Weight	Certifications
Material: Stainless Steel 302 (EN 1.4324), Stainless Steel 304 (EN 1.4301)						
223681300S	1/2"	12.7 mm	1/2 UNC	3.05 m	3.0 kg	-
223683400S	3/4"	19.1 mm	3/4 UNC	3.05 m	6.8 kg	cULus
223683450S	3/4"	19.1 mm	3/4 UNC	1.52 m	3.1 kg	-
223684400S	1"	25.4 mm	1 UNC	3.05 m	12.1 kg	-
223685800S	5/8"	16.0 mm	5/8 UNC	3.05 m	4.7 kg	cULus
223685880S	5/8"	16.0 mm	5/8 UNC	2.44 m	3.5 kg	UL
Material: Stainless Steel 316 (EN 1.4401)						
223683400S316	3/4"	19.1 mm	3/4 UNC	3,000.00 mm	6.3 kg	cULus

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.