


Stainless Steel Ground Rod, Pointed



- For use in highly-corrosive soils



Material: Stainless Steel 304 (EN 1.4301)

Tensile Strength: 586 MPa Min



Part Number	Ground Rod Diameter, Nominal	Ground Rod Diameter, Actual Ø	Length L	Unit Weight	UPC Label	Certifications
223681300	1/2"	12.7 mm	3.05 m	3.0 kg	No	-
223685880	5/8"	15.9 mm	2.44 m	3.8 kg	No	UL
223685800	5/8"	15.9 mm	3.05 m	4.7 kg	No	cULus
223683450	3/4"	19.1 mm	1.52 m	3.1 kg	No	-
223683480	3/4"	19.1 mm	2.44 m	4.6 kg	No	UL
223683400	3/4"	19.1 mm	3.05 m	6.8 kg	No	cULus
223683412	3/4"	19.1 mm	3.66 m	8.6 kg	No	-
223684400	1"	25.4 mm	3.05 m	12.1 kg	No	-
223684415	1"	25.4 mm	4.57 m	13.6 kg	No	-
223GRS141500	-	14.0 mm	1,500.00 mm	1.5 kg	No	-

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.